

# SAFETY DATA SHEET



---

## BOILER WELD Liquid Stop-Leak

SDS Date: 2018-02-23

---

---

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

---

**Company Identification:** UTILITY Enterprises, Inc.  
700 Main Street  
Westbury, NY 11590

**24 Hour Emergency Telephone Number:** Infotrac: 1-800-535-5053

**Product Identifier:** BOILER WELD Liquid  
Stop-Leak

**Product Use:** Liquid boiler stop leak

# BOILER WELD Liquid Stop-Leak

---

## 2. HAZARDS IDENTIFICATION

---

**OSHA REGULATORY STATUS:** This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

\*\*\*\*\*

### EMERGENCY OVERVIEW:

**Color:** Blue-green tint  
**Physical state:** Liquid  
**Appearance:** Clear to opaque  
**Odor:** Odorless to slight odor

**Signal Word:** **WARNING**

**MAJOR HEALTH HAZARDS:** CAUSES SERIOUS EYE IRRITATION. CAUSES SKIN IRRITATION. HARMFUL IF SWALLOWED.

**PHYSICAL HAZARDS:** Upon drying forms thin glass that can cut skin. Spilled material may cause slipping hazard.

**PRECAUTIONARY STATEMENTS:** Wear protective gloves, protective clothing, eye, and face protection as appropriate. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product.

**ADDITIONAL HAZARD INFORMATION:** Toxicity may be delayed, and may not be readily visible. Significant exposures must be referred for medical attention immediately. There is no specific antidote.

\*\*\*\*\*

---

### GHS CLASSIFICATION:

GHS: CONTACT HAZARD - SKIN:	Category 2 - Causes skin irritation.
GHS: CONTACT HAZARD - EYE:	Category 2A - Causes serious eye irritation
GHS: ACUTE TOXICITY - INHALATION:	No data available Not classified
GHS: ACUTE TOXICITY - ORAL:	Category 4 - Harmful if swallowed.
GHS: ACUTE TOXICITY - DERMAL:	Not classified as acutely toxic for dermal exposure.
GHS: CARCINOGENICITY:	Not classified as a carcinogen per GHS criteria. This product is not classified as a carcinogen by NTP, IARC, or OSHA.

**UNKNOWN ACUTE TOXICITY:**  
Not applicable. This product was tested as a whole. This information only pertains to untested mixtures.

**GHS SYMBOL:**  
Exclamation mark

# BOILER WELD Liquid Stop-Leak



**GHS SIGNAL WORD:** WARNING

**GHS HAZARD STATEMENTS:**

**GHS - Health Hazard Statement(s)**

Causes serious eye irritation  
Causes skin irritation  
Harmful if swallowed

**GHS - Precautionary Statement(s) - Prevention**

Wear eye protection/face protection  
Wear protective gloves  
Wash thoroughly after handling  
Do not eat, drink or smoke when using this product

**GHS - Precautionary Statement(s) - Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
IF ON SKIN: Wash with plenty of water  
If skin irritation occurs: Get medical advice/attention  
Take off contaminated clothing and wash it before reuse  
IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
Rinse mouth  
Specific treatment (see First Aid information on product label and/or Section 4 of the SDS)

**GHS - Precautionary Statement(s) - Storage**

There are no Precautionary-Storage phrases assigned

**GHS - Precautionary Statement(s) - Disposal**

Dispose of contents and container in accordance with applicable local, regional, national, and/or international regulations.

**Hazards Not Otherwise Classified (HNOC)**

None identified

**See Section 11: TOXICOLOGICAL INFORMATION**

---

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

---

## BOILER WELD Liquid Stop-Leak

Component	Percent [%]	CAS Number
Water	10 - 40	7732-18-5
Sodium silicate	60 - 90	1344-09-8

---

### 4. FIRST AID MEASURES

---

**INHALATION:** If inhaled and adverse effects occur, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a Poison Center or seek medical attention if you feel unwell.

**SKIN CONTACT:** If on skin, wash with plenty of water. If skin irritation occurs, get medical advice/attention.  
**SPECIFIC TREATMENT:** Wash with lots of water. Take off contaminated clothing and wash before reuse.

**EYE CONTACT:** If in eyes, immediately rinse eyes cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, get medical advice/attention.

**INGESTION:** If swallowed, rinse mouth. Contact a Poison Center, or a doctor/physician, or get medical attention if you feel unwell.

**Most Important Symptoms/Effects (Acute and Delayed)** Solutions of sodium silicate are alkaline. Exposure to alkaline solutions may result in irritation to any contacted tissue, including possible burns, depending on the concentration, duration, and nature of the exposure. This material is not a crystalline silica, and it does not cause pulmonary silicosis.

**Acute Symptoms/Effects:** Listed below.

**Inhalation (Breathing):** Respiratory System Effects: Inhalation of this material may cause irritation, redness of upper and lower airways, coughing.

**Skin:** Skin Irritation. Skin exposure may cause irritation, redness, itching, swelling, burning sensation.

**Eye:** Eye Irritation: Eye exposure may cause severe irritation, and pain. The full extent of injury may not be immediately apparent.

**Ingestion (Swallowing):** Gastrointestinal System Effects: Exposure by ingestion may cause irritation, swelling, and perforation of upper and lower gastrointestinal tissues. Permanent scarring may occur.

**Delayed Symptoms/Effects:**

- Repeated and prolonged skin contact may cause a dermatitis

**Interaction with Other Chemicals Which Enhance Toxicity:** None known.

**Medical Conditions Aggravated by Exposure:** May aggravate preexisting conditions such as: Eye disorders that decrease tear production or have reduced integrity. Skin disorders that compromise the integrity of the skin such as: psoriasis, rashes, eczema, skin infections. Pulmonary disorders that compromise the integrity of the lungs such as asthma.

**Protection of First-Aiders:** Avoid contact with skin and eyes. Use personal protective equipment. Refer to Section 8 for specific personal protective equipment recommendations. At minimum, treating personnel should utilize PPE sufficient for prevention of bloodborne pathogen transmission.

## BOILER WELD Liquid Stop-Leak

---

**Notes to Physician:** Treat as a corrosive substance. Treat symptoms with supportive care. There is no specific antidote. The absence of visible signs or symptoms of burns does NOT reliably exclude the presence of actual tissue damage. It may take 48-72 hours to assess the extent of an ocular burn. Probable mucosal damage may contraindicate the use of gastric lavage.

---

### 5. FIRE-FIGHTING MEASURES

---

**Fire Hazard:** Negligible fire hazard.

**Extinguishing Media:** Use media appropriate for surrounding fire.

**Fire Fighting:** Move container from fire area if it can be done without risk. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas.

**Sensitivity to Mechanical Impact:** Not sensitive.

**Sensitivity to Static Discharge:** Not sensitive.

**Lower Flammability Level (air):** Not flammable

**Upper Flammability Level (air):** Not flammable

**Flash point:** Not flammable

**Auto-ignition Temperature:** Not applicable

---

### 6. ACCIDENTAL RELEASE MEASURES

---

**Personal Precautions:**

Avoid contact with skin and eyes. Avoid breathing fumes, vapor, mist, or spray. Dries to form glass film which can easily cut skin. Spilled material may cause a slipping hazard. Wear appropriate personal protective equipment recommended in Section 8, Exposure Controls / Personal Protection, of the SDS.

**Methods and Materials for Containment and Cleaning Up:**

Flush spill area with water, if appropriate. Liquid material may be removed with a vacuum truck. Shovel dried residue into suitable container. Recycle or dispose according to regulations. See Section 13, Disposal considerations, for additional information.

**Environmental Precautions:**

This material is alkaline and may raise the pH of surface waters with low buffering capacity. Keep out of water supplies and sewers. Releases should be reported, if required, to appropriate agencies.

---

---

# BOILER WELD Liquid Stop-Leak

---

## 7. HANDLING AND STORAGE

---

### Precautions for Safe Handling:

Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. Avoid breathing vapor, mist, or spray. Product shipped/handled hot can cause thermal burns. Use care when handling hot material. Do not eat, drink or smoke in areas where this material is used. Use appropriate personal protective equipment (PPE). See Section 8, Exposure Controls and Personal Protection, for additional information.

### Safe Storage Conditions:

Store and handle in accordance with all current regulations and standards. Keep container tightly closed and properly labeled. Do not store in aluminum container or use aluminum fittings or transfer lines, as flammable hydrogen gas may be generated. Keep separated from incompatible substances (see below or Section 10 of the Safety Data Sheet).

### Incompatibilities/ Materials to Avoid:

Can generate heat when mixed with acids, Avoid prolonged contact with alkali sensitive metals such as: aluminum, brass, bronze, copper, lead, tin, zinc because flammable hydrogen gas can be generated

---

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

---

**Regulatory Exposure Limit(s):** None. This product does not contain any components that have regulatory occupational exposure limits (OEL's) established.

*OEL: Occupational Exposure Limit; OSHA: United States Occupational Safety and Health Administration; PEL: Permissible Exposure Limit; TWA: Time Weighted Average; STEL: Short Term Exposure Limit*

**NON-REGULATORY EXPOSURE LIMIT(S):** Listed below for the product components that have advisory (non-regulatory) occupational exposure limits (OEL's) established.

- *The Non-Regulatory United States Occupational Safety and Health Administration (OSHA) limits, if shown, are the Vacated 1989 PEL's (vacated by 58 FR 35338, June 30, 1993).*

- The American Conference of Governmental Industrial Hygienists (ACGIH) is a voluntary organization of professional industrial hygiene personnel in government or educational institutions in the United States. The ACGIH develops and publishes recommended occupational exposure limits each year called Threshold Limit Values (TLVs) for hundreds of chemicals, physical agents, and biological exposure indices.

<b>OXY REL 8 hr TWA</b>	2 mg/m <sup>3</sup> recommended Time Weighted Average - 8 hour (internal Occupational Exposure Limit)
-----------------------------	---

**ENGINEERING CONTROLS:** Provide local exhaust ventilation where dust or mist may be generated. Ensure compliance with applicable exposure limits.

**PERSONAL PROTECTIVE EQUIPMENT:**

---

## BOILER WELD Liquid Stop-Leak

**Eye Protection:** Wear safety glasses with side-shields. If eye contact is likely, wear chemical resistant safety goggles. Wear chemical safety goggles with a face-shield to protect against eye and skin contact when appropriate. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

**Skin and Body Protection:** Wear protective clothing to minimize skin contact. When skin contact is likely, wear Tychem® SL or a similar protective suit. Wear appropriate heat resistant clothing when potential exists for contact with hot materials.

**Hand Protection:** Wear appropriate chemical resistant gloves. Consult a glove supplier for assistance in selecting an appropriate chemical resistant glove. Use gloves that are cut resistant if handling dry glass material.

**Protective Material Types:** Butyl rubber, Natural rubber, Neoprene, Nitrile, Tychem® SL, Tyvek®

**Respiratory Protection:** A NIOSH approved respirator with N95 (dust, fume, mist) cartridges may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits, or when symptoms have been observed that are indicative of overexposure. A respiratory protection program that meets 29 CFR 1910.134 must be followed whenever workplace conditions warrant use of a respirator.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

<b>Physical state</b>	Liquid
<b>Appearance:</b>	Clear to opaque
<b>Color:</b>	Blue-green tint
<b>Odor:</b>	Odorless to slight odor
<b>Odor Threshold [ppm]:</b>	No data available.
<b>Molecular Formula:</b>	$x\text{SiO}_2/\text{Na}_2\text{O}$ ( $x \geq 3.0$ by weight)
<b>Decomposition Temperature:</b>	No data available
<b>Boiling Point/Range:</b>	214 - 216 °F (101 - 102 °C)
<b>Freezing Point/Range:</b>	30 °F (-1 °C).
<b>Melting Point/Range:</b>	Not applicable to liquids
<b>Vapor Pressure:</b>	No data available
<b>Vapor Density (air=1):</b>	No data available
<b>Relative Density/Specific Gravity (water=1):</b>	1.20 - 1.61
<b>Density:</b>	10.0 - 13.4 lbs/gal
<b>Water Solubility:</b>	100%
<b>pH:</b>	11.0 - 11.4
<b>Volatility:</b>	> 50%
<b>Evaporation Rate (ether=1):</b>	No data available
<b>Partition Coefficient (n-octanol/water):</b>	No data available
<b>Flash point:</b>	Not flammable
<b>Flammability (solid, gas):</b>	Not applicable
<b>Lower Flammability Level (air):</b>	Not flammable
<b>Upper Flammability Level (air):</b>	Not flammable
<b>Auto-ignition Temperature:</b>	Not applicable
<b>Viscosity:</b>	20 - 1500 cp

---

# BOILER WELD Liquid Stop-Leak

---

---

## 10. STABILITY AND REACTIVITY

---

**Reactivity:** Not reactive under normal temperatures and pressures.

**Chemical Stability:** Stable at normal temperatures and pressures.

**Possibility of Hazardous Reactions:**

Contact with acids will cause gelling and evolution of heat. Prolonged contact with incompatible metals may produce flammable hydrogen gas.

**Conditions to Avoid:**

(e.g., static discharge, shock, or vibration) -. Prolonged storage above 140 °F (60 °C).

**Incompatibilities/ Materials to Avoid:**

Can generate heat when mixed with acids. Avoid prolonged contact with alkali sensitive metals such as: aluminum, brass, bronze, copper, lead, tin, zinc because flammable hydrogen gas can be generated.

**Hazardous Decomposition Products:** None known

**Hazardous Polymerization:** Will not occur.

---

## 11. TOXICOLOGICAL INFORMATION

---

**IRRITATION DATA:** As listed below

**Standard Draize (Eye):** Test results for solutions with the following pH/weight ratio of SiO<sub>2</sub>/Na<sub>2</sub>O are as follows:  
11.6/2.54 = irritant; 11.6/2.4 = irritant; 12.2/2.0 = corrosive; 12.4/1.8 = corrosive

**TOXICITY DATA:**

**PRODUCT TOXICITY DATA:**

<b>LD50 Oral:</b> 1153 mg/kg (Rat)	<b>LD50 Dermal:</b> 4,640 mg/kg (Rabbit)	<b>LC50 Inhalation:</b> No data available
---------------------------------------	---	--

**COMPONENT TOXICITY DATA:**

**Note:** The component toxicity data is populated by the LOLI database and may differ from the product toxicity data given.

<b>Component</b>	<b>LD50 Oral:</b>	<b>LD50 Dermal:</b>	<b>LC50 Inhalation:</b>
Sodium silicate 1344-09-8	1153 mg/kg (Rat)	-----	-----

\*\*\*\*\*

---



# BOILER WELD Liquid Stop-Leak

## POTENTIAL HEALTH EFFECTS:

- Eye contact:** Causes serious eye irritation. Eye exposures may cause burns to the eye lids, conjunctivitis, corneal edema, and corneal burn. The full extent of the injury may not be immediately apparent.
- Skin contact:** Causes skin irritation. Contact with skin may result in redness, itching, irritation, burning sensation, swelling.
- Inhalation:** Inhalation of mist, vapor, or spray may cause irritation of the respiratory tract, possibly with coughing, choking, and pain either immediately or within 72 hours.
- Ingestion:** Harmful if swallowed. May cause immediate pain and severe burns of the upper and lower gastrointestinal tract with vomiting, nausea, and diarrhea.
- Chronic Effects:** Repeated or prolonged skin contact may result in dermatitis.

## SIGNS AND SYMPTOMS OF EXPOSURE:

Solutions of sodium silicate are alkaline. Exposure to alkaline solutions may result in irritation to any contacted tissue, including possible burns, depending on the concentration, duration, and nature of the exposure. This material is not a crystalline silica, and it does not cause pulmonary silicosis.

- Inhalation (Breathing):** Respiratory System Effects: Inhalation of this material may cause irritation, redness of upper and lower airways, coughing.
- Skin:** Skin Irritation. Skin exposure may cause irritation, redness, itching, swelling, burning sensation.
- Eye:** Eye Irritation: Eye exposure may cause severe irritation, and pain. The full extent of injury may not be immediately apparent.
- Ingestion (Swallowing):** Gastrointestinal System Effects: Exposure by ingestion may cause irritation, swelling, and perforation of upper and lower gastrointestinal tissues. Permanent scarring may occur.

**Interaction with Other Chemicals Which Enhance Toxicity:** None known.

\*\*\*\*\*

## GHS HEALTH HAZARDS:

**GHS: ACUTE TOXICITY - ORAL:** Category 4 - Harmful if swallowed.

**GHS: ACUTE TOXICITY - DERMAL:** Not classified as acutely toxic for dermal exposure.

**GHS: ACUTE TOXICITY - INHALATION:** No data available. Not classified.

**Skin Absorbent / Dermal Route?** No.

**GHS: CONTACT HAZARD - SKIN:** Category 2 - Causes skin irritation

**GHS: CONTACT HAZARD - EYE:** Category 2A - Causes serious eye irritation

# BOILER WELD Liquid Stop-Leak

---

-  
**GHS: CARCINOGENICITY:**

Not classified as a carcinogen per GHS criteria. This product is not classified as a carcinogen by NTP, IARC, or OSHA.

---

## 12. ECOLOGICAL INFORMATION

---

**ECOTOXICITY DATA:**

**Aquatic Toxicity:**

This material is believed to be practically non-toxic to aquatic life.

**FATE AND TRANSPORT:**

**BIODEGRADATION:** This material is inorganic and not subject to biodegradation.

**PERSISTENCE:** This material is believed to persist in the environment.

**BIOCONCENTRATION:** This material is not expected to bioconcentrate in organisms.

**ADDITIONAL ECOLOGICAL INFORMATION:** This material has exhibited slight toxicity to terrestrial organisms.

---

## 13. DISPOSAL CONSIDERATIONS

---

**Waste from material:**

Reuse or recycle if possible. May be subject to disposal regulations. Dispose in accordance with all applicable regulations.

**Container Management:**

Dispose of container in accordance with applicable local, regional, national, and/or international regulations. Container rinsate must be disposed of in compliance with applicable regulations.

---

## 14. TRANSPORT INFORMATION

---

**LAND TRANSPORT**

**U.S. DOT 49 CFR 172.101:**

**Status:** Not regulated

---

# BOILER WELD Liquid Stop-Leak

## CANADIAN TRANSPORTATION OF DANGEROUS GOODS:

Status: Not regulated.

## MARITIME TRANSPORT (IMO / IMDG) Not regulated

Status - IMO / IMDG: Not Regulated

---

## 15. REGULATORY INFORMATION

---

### U.S. REGULATIONS

#### **OSHA REGULATORY STATUS:**

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

#### **CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR 302.4):**

Not regulated.

#### **SARA EHS Chemical (40 CFR 355.30)**

Not regulated

#### **EPCRA SECTIONS 311/312 HAZARD CATEGORIES (40 CFR 370.10):**

Acute Health Hazard

#### **EPCRA SECTION 313 (40 CFR 372.65):**

Not regulated.

#### **OSHA PROCESS SAFETY (PSM) (29 CFR 1910.119):**

Not regulated

**FDA:** Sodium Silicates have Generally Recognized as Safe (GRAS) status under specific FDA regulations. Refer to 21 Code of Federal Regulations (CFR) 173, 175, 176, 177, 182, and 184, which is accessible on the FDA's website. This product is not produced under all current Good Manufacturing Practices (cGMP) requirements as defined by the Food and Drug Administration (FDA).

### NATIONAL INVENTORY STATUS

**U.S. INVENTORY STATUS: Toxic Substance Control Act (TSCA):** All components are listed or exempt.

**TSCA 12(b):** This product is not subject to export notification.

**Canadian Chemical Inventory:** All components of this product are listed on either the DSL or the NDSL.

# BOILER WELD Liquid Stop-Leak

## STATE REGULATIONS

### **California Proposition 65:**

This product and its ingredients are not listed, but it may contain impurities/trace elements known to the State of California to cause cancer or reproductive toxicity as listed under Proposition 65 State Drinking Water and Toxic Enforcement Act.

## CANADIAN REGULATIONS

• This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations

### WHMIS - Classifications of Substances:

• D2B - Poisonous and Infectious Material; Materials causing other toxic effects - Toxic material

---

## 16. OTHER INFORMATION

**HMIS: (SCALE 0-4)** (Rated using National Paint & Coatings Association HMIS: Rating Instructions, 2nd Edition)

**Health Rating:** 2

**Flammability Rating:** 0

**Reactivity Rating:** 0

**NFPA 704 - Hazard Identification Ratings (SCALE 0-4)**

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act and shall not be used for any other purpose. **UTILITY** urges the customers receiving this Safety Data Sheet to study it carefully to become aware of the hazards, if any, of the product involved. In the interest of safety, you should notify your employees, agents, and contractors of the information on the sheets. The information herein has been compiled from sources believed to be reliable, up-to-date, and is accurate to the best of our knowledge. However, **UTILITY** cannot give any guarantees regarding information from other sources, and expressly does not make warranties, nor assumes any liability for its use.

---