



# **SECTION 1 - IDENTIFICATION**

Manufacturer: UTILITY

700 Main Street Westbury, NY 11590

Telephone: 1-516-997-6300

Fax: 1-516-997-6345

Web Site: www.UtilityChemicals.com

E-mail: info@UtilityChemical.com

Recommended Use:

For cleaning small drains, grease traps and septic systems

**INFOTRAC** 


(800) 535-5053

24 hours per day - 7 days a week

For any transportation or medical chemical emergencies call:

Product Name:

**CRYSTAL SWIFT Drain Cleaner** 



# **SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS**

Hazardous ChemicalsCAS #EINECS#Approx %SODIUM HYDROXIDE1310-73-2215-185-5100%

Title III Section 313 Supplier Notification: This product contains toxic chemicals subject to the reporting requirement of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40CFR372. This information must be included in all MSDS's that are copied and distributed for this material.

# MATERIAL SAFETY DATA SHEET

#### **SECTION 4 - FIRST-AID MEASURES**

Inhalation: Call a physician or poison control center immediately. Move to fresh air. If not breathing, give artificial respiration.

If breathing is difficult, give oxygen.

**Skin:** Wash off immediately with soap and plenty of water, remove all contaminated clothes and shoes. Consult a physician.

Eyes: Immediate medical attention is required. Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Keep eye wide open while rinsing. Do not rub affected area.

Ingestion: Call a physician immediately. Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting

without medical advice. Never give anything by mouth to an unconscious person.

Note to physician: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of

stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse

pressure. Treat symptomatically.

SECTION 5 - FIRE-FIGHTING MEASURES					
Extinguishing Med Suitable As appropriate.	<u>Unsuitable</u>	Specific Hazards Causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Substance with react with water (some violently), releasing corrosive and/or toxic	Protective Equipment  Self-contained breathing apparatus {(SCBA), MSHA/NIOSH}.  Full protective gear.		
Special Firefighting Procedures  In the event of fire and/or explosion do not breath fumes.					

#### **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Personal Precautions: Use personal protective equipment. Avoid contact with skin, eyes and clothing. Do not touch damaged

containers or spilled materials unless wearing appropriate protective clothing. Avoid dust formation.

Protective Equipment: None. Emergency Procedures: None.

**Environmental Precautions:** Prevent material from entering waterway.

**Methods for Cleaning-Up:** Prevent further leakage or spillage if safe to do so. Prevent dust cloud. Cover powder spill with

plastic sheet or tarp to minimize spreading and keep powder dry. Take up mechanically and collect in suitable container for disposal. Avoid dust formation. Clean contaminated surfaces thorougly.

Other Precautions: Do not get water inside containers. Refer to protective measures listed in Sec. 7 and 8.

# **SECTION 7 - HANDLING AND STORAGE**

<u>Handling</u> <u>Storage</u>

Wear personal protective equipment. Ensure adequate ventilation . Avoid contact with skin, eyes and clothing. Do not breath vapors/dust. Remove and wash contaminated clothing before re-use.

Keep containers tightly closed in a dry and well-ventilated place. Keep in properly labeled containers. Keep out of reach of children.

### MATERIAL SAFETY DATA SHEET

# **SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**OSHA Exposure Limits** 

<u>Hazardous Components</u> SODIUM HYDROXIDE ACGIH-TLV 2 mg/m3

OSHA-PEL 2 mg/m3

### **Personal Protective Equipment**

**Respiratory Protection:** Use NIOSH approved respirators to prevent overexposure.

**Ventilation:** Local ventilation is adequate.

Other Protective Equipment: Protective Gloves

Impervious Gloves. Tightly Fitter

Eyes and Face Protection
Tightly Fitted Safety Goggles

Other Protective Equipment Impervious Clothing.

OR Face Shield.

Other Precautions: None.

#### **Engineering Controls**

Showers. Eyewash stations. Ventilation systems. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes and clothing. Keep away from food, drink and animal feeding stuffs. Remove and wash contaminated clothing before re-use. Regular cleaning of equipment, work area and clothing.

**SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES** 

#### Appearance: White Volatile by Volume: N/A Odor: Odorless Vapor Pressure: N/A Odor Threshold: N/A Vapor Density: N/A pH: **Relative Density:** N/A N/A Melting/Freezing Point: N/A Solubility: Soluble **Boiling Point:** Partition Coefficient: n-octanol/water: 1390°C / 2534°F N/A

**Boiling Range:** N/A Auto-ignition Temperature: N/A Flash Point: Specific Gravity (H20=1): N/A 2.1 **Evaporation Rate:** N/A Viscosity: N/A Flammability: VOC: N/A 0 g/l

Flammability Limits: LEL: N/A; UEL: N/A

SECTION 10 - STABILITY AND REACTIVITY				
Stability Stable Unstable	Hazardous Polymerization May Occur Will Not Occur	<u>Conditions To Avoid</u> Exposure to air or moisture over prolonged periods.  Avoid dust formation.		
Incompatible Materials		<b>Hazardous Decomposition Products</b>		
Aluminum, Tin, Lead, Zinc, and their alloys and all acids.		Reaction with various food sugars may form carbon dioxide.		

# MATERIAL SAFETY DATA SHEET

SECTION 11 - TOXICOLOGICAL INFORMATION				
Likely Routes of Exposure	Symptoms/Effects			
Inhalation 🗸	Harmful by inhalation. Inhalation of corrosive fumes/gases may cause coughing, choking,			
	headache, dizziness, and weakness for several hours. Pulmonary edema may occur			
	with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure,			
	and increased heart rate. Aspiration into lungs can produce severe lung damage.			
Skin Contact	Causes burns.			
Eye Contact	Causes burns. Corrosive to the eyes and may cause severe damage including blindness.			
Ingestion	Harmful if swallowed. Ingestion causes burns of the upper digestive and respiratory tract.			
	Can burn mouth, throat, and stomach.			
Long-Term Effects: N/A	, , , , , , , , , , , , , , , , , , ,			
Medical conditions aggravated I	ov exposure: None.			
Toxicity				
Hazardous Components	LD50 LC50			
SODIUM HYDROXIDE	Oral : 140 mg/kg (rat) ; Dermal : 1,350 mg/kg (rabbit) N/A			
SODIOM HTDROXIDE Oral : 140 hig/kg (lat) , Definal : 1,330 hig/kg (labbit) N/A				
SECTION 12 - ECOLOGICAL INFORMATION				
Ecotoxicity:	None.			
Persistance & Degradability:	None.			
Bioaccumulative Potential:	None.			
Mobility in Soil:	None.			
Other Adverse Effects:	Possible risks of irreversible effects.			

# **SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal should be made in accordance with federal, state and local regulations.

# **SECTION 14 - TRANSPORTATION INFORMATION**

# **Shipping Information**

Shipping Name: Sodium Hydroxide Solid

**Hazardous Class:** 

I.D. Number: UN1823

Packing Group:

Label Required: Corrosive

Marine Pollutant: Nο

**Exception:** This product, when packaged and distributed in a quantity and form intended or suitable for retail sale and designed for consumption by individuals for their personal care or household use purposes, may qualify as a "Consumer Commodity". As such, it can then be exempted from certain labeling, packaging and shipping requirements.

# **SECTION 15 - REGULATORY INFORMATION**

None.

# **SECTION 16 - OTHER INFORMATION**

Disclaimer: **Revision Date:** 2017-05-11

Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act and shall not be used for any other purpose. UTILITY urges the customers receiving this Material Safety Data Sheet to study it carefully to become aware of the hazards, if any, of the product involved. In the interest of safety, you should notify your employees, agents, and contractors of the information on the sheets. The information herein has been compiled from sources believed to be reliable, up-to-date, and is accurate to the best of our knowledge. However, UTILITY cannot give any guarantees regarding information from other sources, and expressly does not make warranties, nor assumes any liability for its use. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or guality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified.