






UTILITY

SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION

Manufacturer: UTILITY 700 Main Street Westbury, NY 11590 Telephone: 1-516-997-6300 Fax: 1-516-997-6345 Web Site: www.UtilityChemicals.com E-mail: info@UtilityChemical.com	For any transportation or medical chemical emergencies call: <p style="text-align: center;">INFOTRAC</p> <p style="text-align: center;">(800) 535-5053</p> <p style="text-align: center;">24 hours per day - 7 days a week</p>
Product Name: Liquid Drain-A-Matic Drain Opener	Recommended Use: For clearing drains of hair, grease, paper, lint and organic matter.

SECTION 2 - HAZARD(S) IDENTIFICATION

 Corrosive	 Poison	NFPA 	HMIS <table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td style="background-color: #000080; color: white;">HEALTH</td><td style="background-color: #000080; color: white; text-align: center;">3</td></tr> <tr><td style="background-color: #FF0000; color: white;">FLAMMABILITY</td><td style="background-color: #FF0000; color: white; text-align: center;">0</td></tr> <tr><td style="background-color: #FFD700; color: black;">REACTIVITY</td><td style="background-color: #FFD700; color: black; text-align: center;">1</td></tr> </table> <p style="text-align: center;">PPE H</p>	HEALTH	3	FLAMMABILITY	0	REACTIVITY	1
HEALTH	3								
FLAMMABILITY	0								
REACTIVITY	1								
HEALTH HAZARD 4 Deadly 3 Extreme Danger 2 Hazardous 1 Slightly Hazardous 0 Normal Material	FIRE HAZARD Flash Points 4 Below 73°F (Boiling pt. below 100°F) 3 Below 73°F (Boiling pt. at/above 100°F) and/or at/above 73°F - not exceeding 100°F 2 Above 100°F, Not exceeding 200°F 1 Above 200°F 0 Will not burn	INSTABILITY 4 May detonate 3 Shock and heat may detonate 2 Violent chemical changes 1 Unstable if heated 0 Stable	SPECIFIC HAZARD Oxidizer OX Use NO WATER W Simple Asphyxiant SA						
Health Acute Toxicity: Cat. 5 Skin Corrosion: Cat. 1 Eye Irritation: Cat. 2B Skin Sensitization: NO	Environmental Acute Toxicity: N/A Chronic Toxicity: N/A	Physical Flammability: N/A Other: N/A							
Hazardous Statement Poison! Causes severe burns. Harmful or fatal if swallowed.		Precautionary Statement Avoid contact with skin and eyes. Keep out of reach of children. Do not allow to be taken internally. Protect face (especially eyes) and other parts of body when using.							

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

<u>Hazardous Chemicals</u>	<u>CAS #</u>	<u>EINECS#</u>	<u>Approx %</u>
POTASSIUM HYDROXIDE	1310-58-3	215-181-3	5-50%
SODIUM HYDROXIDE	1310-73-2	215-185-5	5-50%

*Title III Section 313 Supplier Notification: This product contains toxic chemicals subject to the reporting requirement of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40CFR372. This information must be included in all MSDS's that are copied and distributed for this material.

MATERIAL SAFETY DATA SHEET

SECTION 4 - FIRST-AID MEASURES

Inhalation: Remove from further exposure. Keep warm and at rest. If not breathing, give artificial respiration. If breathing is difficult, trained personnel should administer oxygen. Seek immediate medical attention.

Skin: Remove contaminated clothing including shoes and immediately wash affected area with plenty of soap and water. Seek immediate medical attention. Wash contaminated clothing and shoes before reuse.

Eyes: Immediately flush eyes with plenty of water for two to three minutes. Remove any contact lenses and continue flushing for 15 minutes. Get immediate medical attention.

Ingestion: Wash out mouth with water, keep at rest. Seek immediate medical attention. DO NOT induce vomiting unless directed to do so by medical personnel.

SECTION 5 - FIRE-FIGHTING MEASURES

<u>Extinguishing Media</u>		<u>Specific Hazards</u>	<u>Protective Equipment</u>
<u>Suitable</u>	<u>Unsuitable</u>		
Water Spray Dry Chemical Standard Agents	-----	Sodium Hydroxide will react with metals such as aluminum, tin, and zinc to generate flammable and explosive hydrogen gas.	Self-contained breathing apparatus {(SCBA), MSHA/NIOSH}. Full protective gear.

Special Firefighting Procedures

Avoid direct contact of Sodium Hydroxide with water, as this can produce a violent exothermic reaction. Use water to cool containers exposed to fire. Contact with reactive metals may result in the generation of flammable gas.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions: None.

Protective Equipment: None.

Emergency Procedures: None.

Environmental Precautions: Keep out of water sources and sewers.

Methods for Cleaning-Up: If possible, dike spill and mop or pump into plastic or lacquer lined drums, label "Corrosive" and store away from heat and out of direct sunlight. Residual may be neutralized with citric acid.

Other Precautions: None.

SECTION 7 - HANDLING AND STORAGE

<u>Handling</u>	<u>Storage</u>
Wear appropriate personal protective equipment when handling Sodium Hydroxide and Potassium Hydroxide.	Store in a dry place in accordance with 29 CFR 1910.106 and away from acids, metals, explosives, organic compounds and flammable materials. Do not store in containers made from tin, aluminum, zinc and alloys containing these metals.

MATERIAL SAFETY DATA SHEET

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

OSHA Exposure Limits

Hazardous Components
 POTASSIUM HYDROXIDE
 SODIUM HYDROXIDE

ACGIH-TLV
 2 mg/m3
 2 mg/m3

OSHA-PEL
 N/A
 3 mg/m3

Personal Protective Equipment

Respiratory Protection: Use NIOSH approved respirators to prevent overexposure.

Ventilation: Local ventilation is adequate.

Other Protective Equipment:	<u>Protective Gloves</u> Neoprene/Chemical Resistant Gloves.	<u>Eyes and Face Protection</u> Chemical Safety Goggles and Face Shield.	<u>Other Protective Equipment</u> Chemical Suit, Rubber Boots.
------------------------------------	---	---	---

Other Precautions: None.

Engineering Controls

Avoid contact with face and skin. Cleanse skin thoroughly after contact, before meals and at end of work period. Impervious chemical resistant clothing should be worn.

SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES

<p>Appearance: Clear</p> <p>Odor: Odorless</p> <p>Odor Threshold: N/A</p> <p>pH: 14</p> <p>Melting/Freezing Point: N/A / N/A</p> <p>Boiling Point: 265°F</p> <p>Boiling Range: N/A</p> <p>Flash Point: N/A</p> <p>Evaporation Rate: N/A</p> <p>Flammability: N/A</p> <p>Flammability Limits: LEL: N/A ; UEL: N/A</p>	<p>Volatile by Volume: N/A</p> <p>Vapor Pressure: N/A</p> <p>Vapor Density: N/A</p> <p>Relative Density: N/A</p> <p>Solubility: Complete</p> <p>Partition Coefficient: n-octanol/water: N/A</p> <p>Auto-ignition Temperature: N/A</p> <p>Specific Gravity (H2O=1): 1.44</p> <p>Viscosity: N/A</p> <p>VOC: 0 g/l</p>
---	---

SECTION 10 - STABILITY AND REACTIVITY

<p>Stability</p> <p>Stable Unstable</p> <p><input checked="" type="checkbox"/> <input type="checkbox"/></p>	<p>Hazardous Polymerization</p> <p>May Occur Will Not Occur</p> <p><input type="checkbox"/> <input checked="" type="checkbox"/></p>	<p style="text-align: center;">Conditions To Avoid</p> <p>Mixing with water, acid, or incompatible materials can cause splattering and release of large amounts of heat.</p>
<p style="text-align: center;">Incompatible Materials</p> <p>Acids, aluminum, tin, zinc, and alloys containing these metals, iron, copper, wool, leather, clothing materials, organic chemicals such as nitrocarbons and halogenated hydrocarbons, carbohydrates, phosphorous, explosives and organic peroxides.</p>	<p style="text-align: center;">Hazardous Decomposition Products</p> <p>Carbon monoxide with carbohydrates, hydrogen with aluminum, tin and zinc.</p>	

MATERIAL SAFETY DATA SHEET

SECTION 11 - TOXICOLOGICAL INFORMATION

<u>Likely Routes of Exposure</u>	<u>Symptoms/Effects</u>	
Inhalation <input checked="" type="checkbox"/>	Causes respiratory irritation which may develop into serious lung injury depending upon the degree of exposure. Corrosive. Can cause severe skin burns. Irritation may not be immediately painful. Greater exposure results in severe burns with scarring. Corrosive. Can cause severe eye burns. Contact results in immediate pain and can cause permanent eye damage including blindness. Corrosive. Contact will cause severe burns of the mouth, throat and stomach.	
Skin Contact <input checked="" type="checkbox"/>		
Eye Contact <input checked="" type="checkbox"/>		
Ingestion <input checked="" type="checkbox"/>		
Long-Term Effects: N/A		
Hazardous Components	Toxicity	LC₅₀
POTASSIUM HYDROXIDE	LD ₅₀ Oral: 365 mg/kg (rat)	N/A
SODIUM HYDROXIDE	Oral: 500 mg/kg (rabbit)	N/A

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity:	None.
Persistence & Degradability:	None.
Bioaccumulative Potential:	None.
Mobility in Soil:	None.
Other Adverse Effects:	None.

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

SECTION 14 - TRANSPORTATION INFORMATION

<u>Shipping Information</u>		Exception: This product, when packaged and distributed in a quantity and form intended or suitable for retail sale and designed for consumption by individuals for their personal care or household use purposes, may qualify as a "Consumer Commodity". As such, it can then be exempted from certain labeling, packaging and shipping requirements.
Shipping Name:	Sodium Hydroxide, Solution	
Hazardous Class:	8	
I.D. Number:	UN1824	
Packing Group:	II	
Label Required:	Corrosive	
Marine Pollutant:	No	

SECTION 15 - REGULATORY INFORMATION

None.

SECTION 16 - OTHER INFORMATION

Disclaimer :

Revision Date: 2017-05-11

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act and shall not be used for any other purpose. UTILITY urges the customers receiving this Safety Data Sheet to study it carefully to become aware of the hazards, if any, of the product involved. In the interest of safety, you should notify your employees, agents, and contractors of the information on the sheets. The information herein has been compiled from sources believed to be reliable, up-to-date, and is accurate to the best of our knowledge. However, UTILITY cannot give any guarantees regarding information from other sources, and expressly does not make warranties, nor assumes any liability for its use.