


AQUA-PLUG




LEAK STOPPING CEMENT

Stops Running Water Leaks
Prevents Water Seepage Through Masonry



AQUIA-PLUG, leak stopping cement, is a fast setting hydraulic compound used for filling holes, cracks or leaks in masonary floors and walls. AQUIA-PLUG sets under water and is the ideal cement for stopping water infiltration.







Item# Size

30-6520 12 - 3 LB. CONTAINERS 30-6530 4 - 10 LB. CONTAINERS 30-6550 1 - 50 LB. CONTAINER SETS UNDER WATER
USE TO PATCH
SWIMMING POOLS

DIRECTIONS

To fill cracks or holes in concrete:

- Area to be patched must be clean and free of any loose material. Deepen cracks for more secure anchoring.
- 2. Mix product to a putty like consistency. AQUIA-PLUG sets in 3-5 minutes, so mix only enough for immediate use.
- 3. Force product into crack or hole using putty knife or trowel. Hold in place for a few minutes until AQUIA-PLUG has set.
- 4. For water running through walls: Start at top of crack and work your way down. Gradually reduce size of opening by pressing AQUIA-PLUIG firmly into crack and holding in place until set. Repeat procedure until crack is closed.

STORAGE: Store in a cool, dry place.