




# FUEL TANK WATER ABSORBER



A NECESSITY FOR ALL FUEL OIL TANKS

Prevents Freeze-ups  
Reduces Corrosion  
Dissolves Gum & Sludge  
Absorbs twice its weight in water  
Inhibits the growth of algae and bacteria  
Prevents rust

ITEM#  
12-1 qt. containers 20-1020  
6-1 gal. containers 20-1030  
other sizes available

## UTILITY

700 MAIN STREET  
WESTBURY, NY 11590 U.S.A.  
(516) 997-6300  
FAX# (516) 997-6345  
[www.UtilityChemicals.com](http://www.UtilityChemicals.com)

**Hy-Dro-Sol** is designed to absorb and permanently disperse water in fuel oil and eliminate the problems that go hand-in-hand with water conditions such as: freeze-ups, corrosion and water based sludge.

Condensation is the most common source of water in oil. Oil pumped from a cold delivery truck into a warm basement causes condensation. Oil in outdoor or in ground tanks is commonly colder than the air temperature in the morning, this also causes condensation. Water can also enter an oil tank during a rain or snow storm. Much of the sludge in oil is produced by algae. Eliminating the water eliminates the algae and eliminates the sludge. Water can also separate the gum in oil which builds up on burner parts as varnish. **Hy-Dro-Sol** attacks the water molecules, breaking them apart and making them as light as the oil molecules.

Use **Hy-Dro-Sol** as a preventative treatment. Agitation is necessary for best results, therefore add **Hy-Dro-Sol** immediately before delivery of oil. Use one quart for a 275 gallon tank, two quarts for a 550 gallon tank and one gallon for a 1,000 gallon tank. For each additional 1,000 gallon capacity, use 1 more gallon of **Hy-Dro-Sol**.