


WAX BOWL GASKET



ITEM #16-505

FITS ALL STANDARD CLOSET BOWLS




Also **WITH PLASTIC SLEEVE FLANGE**



ITEM #16-510

FITS 3" & 4" WASTE LINES



- ◆ Forms a permanent gas-tight, water-tight and odor-tight sanitary seal.
- ◆ Made of 100% pure wax.
- ◆ Fits all standard closet bowls.
- ◆ Gasket with Plastic Sleeve Flange provides positive bowl alignment.
- ◆ Will not dry out, harden, crack or deteriorate.
- ◆ Packed in plastic tray to preserve shape and eliminate messy handling.
- ◆ Conforms to Federal Specification A-A-3110.

INSTRUCTIONS:

Use **UTILITY WAX BOWL GASKET** at room temperatures (approx. 75°F.) to allow adequate distribution of wax.

- 1.) Place bowl upside down on padded surface. Then put **UTILITY WAX BOWL GASKET** around discharge opening and press firmly into place to assure proper adhesion.
- 2.) Carefully lift bowl over the toilet flange, line it up with the flange bolts and set in place. Press down firmly and tighten the bolts carefully to avoid cracking the bowl.



UTILITY

700 MAIN STREET
WESTBURY, NY 11590 U.S.A.
(516) 997-6300
FAX# (516) 997-6345
www.UtilityChemicals.com

